



Declaration of Compliance

Business Operator

CEJN AB
Rattvägen 1
P.O. Box 245
SE-541 25 Skövde
Sweden
Tel. +46 (0) 500 47 75 00

Information given in this declaration is based on our current state of knowledge and written confirmation from our suppliers.

Product name

CEJN Detect Stop Ball



This DoC applies to the following products

The complete range of CEJN Detect stop balls.

Materials

Polyamide 66, Thermoplastic elastomer and AISI304.

Color

Grey blue

EU Compliance

Reg. (EC) No 1935/2004

In accordance with EU Commission Regulation no. 1935/2004, Food contact material (FCM).

The intended use of the stop ball is for use on compressed air hoses and washdown hoses in the food industry with unintended contact with food.

Reg. (EU) No 2023/2006

The product is produced according to EU Commission Regulation no. 2023/2006 of 22 December 2006 on good manufacturing practices for materials and articles intended to come into contact with food (GMP).

AP(89)1

Although the positive list set out in Annex I of Commission Regulation (EU) No 10/2011, and further amendments until Reg. (EU) 2020/1245, does not include the colorants, we hereby confirm that those eventually included in the formulation of the

product are in compliance with the purity requirements defined in the resolution AP(89)1 of 13 September 1989 of the Council of Europe on the use of colorants in plastic materials coming into contact with food.

Reg. (EU) No 10/2011

The plastic material (Polyamide 66) is composed exclusively by substances listed in the positive list of the following regulations relating materials and items intended to come into contact with foodstuffs: Regulation (EU) No 10/2011. Subsequent amendments up to (EU) 2023/1627 are included.

The material contains intentionally added additives for which restrictions or purity criteria are in place in accordance with Reg. (EU) No 10/2011. Upon request we will supply relevant information regarding these substances on a confidential basis.

Reg. (EC) No 1333/2008

The material contains intentionally added "dual use" additives according to Reg. (EC) No 1333/2008. Upon request we will supply relevant information regarding these additives on a confidential basis.

US FDA Compliance

All raw materials in this product are in compliance with FDA (Food and Drug Administration in the USA) 21 CFR parts 170 to 199.

The polymers and additives complies with FDA 21 CFR part 175, 177, and 178. Additives are cleared according to FDA 21 CFR Part 178 (Indirect food additives), are generally recognized as safe (GRAS).

The colorants in the compound are listed under FDA 21 CFR 178.3297 "Colorants for Polymers".

Migration analysis

The plastic material (outer shell) passes both the EU and FDA migration tests.

Migration analysis report

Samples of the product (outer shell) have been tested for overall migration according to the test conditions specified in (EU) No 10/2011.

The results for overall migration are below the threshold value of 10 mg/dm² and the migration did not increase from 1st to the 2nd and from the 2nd to the 3rd migration.

The results for specific migration are below the specific migration limits and the migration did not increase from the 1st to the 2nd and from the 2nd to the 3rd migration.

In the scope of the NIAS Screening there was no indication for an objection.

Food simulants used for overall migration were 10 % ethanol, 95% ethanol, 3 % acetic acid, and olive oil.
Test conditions for overall migration: 3 x 30 min at 40°C.
(Repeated use)

Max ratio of food contact surface area to volume 1.0 dm²/100 ml

Food contact The intended use of the stop ball is for use on compressed air hoses and washdown hoses in the food industry with unintended contact with food.

Usage temperature Minimum temperature: -20°C (-4°F)
Maximum temperature: 60°C (140°F)

General Equipment should be cleaned and disinfected, as appropriate to its intended use, before use.

It is also important to clean and disinfect equipment as appropriate after use, using the appropriate decontamination chemicals, concentrations, times and temperatures.

Appropriate equipment decontamination will minimize the risk of microbial growth and cross contamination and will maximize the efficiency and durability of the equipment.

We will make the relevant background documentation available to the competent authorities, at their request.


Materials

Plastic As stated above, the plastic material in the stop ball is considered food approved (Food-grade).

Screws In Food-grade AISI304.

Date 3rd of February 2026

Made by



Joachim Schröter
Segment Manager – Food & Beverage Industry